

ATLANTA - FIXING AND CARE INSTRUCTIONS

IMPORTANT - Please read these instructions before starting work

1. Check that there are no buried pipes or cables before drilling any holes. Take extreme care when using electrical equipment near water.
2. Do not fix accessories onto newly papered or painted surface as chemical reactions could cause discolouration to the products. (Please refer to manufacturer's instructions).
3. We recommend the use of a special drill bit when fixing accessories to a tiled area.

SUPPLIED FIXINGS:



FIXING INSTRUCTIONS

1. Establish position for accessories, making sure there is sufficient room.
2. Use the allen key (2) to loosen the grub screw in the upright pillar and remove the wall fixing plate.
3. Hold the Wall fixing plate in the required position, ensuring the arrow is pointing 'UP', & mark through the holes with a pencil. If two back plates are necessary, mark the position of the first back plate & then carefully measure the distance between the upright centers, ensuring the marks are horizontal by use of a spirit level. Care should be taken when drilling.
4. Drill holes to a depth of 35 mm using a 5.5 mm masonry drill and insert the wall plugs so they are flush with the wall. (NOTE: The wall plugs provided are recommended for **SOLID WALLS** only. If using on plasterboard or hollow walls, specialist fixings **ARE** required. These can be obtained from a DIY outlet).
5. Fix the wall fixing plate to the wall with the screws provided, then replace the upright, making sure the grub screw faces directly downwards before tightening.

CARE INSTRUCTIONS

We recommend regular cleaning with a mild soap liquid and drying with a soft cloth. The use of abrasive cleaners or bleach will damage the finish. Your bathroom should be ventilated to prevent condensation.



PLEASE NOTE:

These measurements are for guidance only and may vary on individual production runs, items **MUST always** be measured prior to fitting.

+	Shelf, 8802C 380 mm	+	Towel Rail, 8806C 455 mm	+
+	Four Hook Panel, 8808C 196 mm	+	Long Towel Rail, 8816C 605 mm	+
+	Double Towel Rail, 8827C 605 mm	+	Toilet Roll Holder, 8837C 150 mm	+

All 'centres' refer to the back plate upright centres.

**PLEASE CHECK THE EXACT MEASUREMENT ON THE
PRODUCT YOU ARE FITTING**



This product is guaranteed against defects which affect its use which are due to faulty workmanship or materials. This guarantee is strictly limited to domestic users only. If you wish to claim please return the product to the dealer with proof of purchase. Only the original purchaser may claim under this guarantee.

For full details please visit our website www.millerbathrooms.co.uk